

FACTORY PREPARED TECHNICAL SERVICE DATA

MODEL: AS41W

SERVICE PUBLICATIONS DEPARTMENT Entertainment Products Division · Sylvania Electric Products Inc. · 700 Ellicott Street · Batavia, N.Y.

The AS41W is a small component, "air suspension" sealed speaker system incorporating a 4" high compliance wide range driver.

REMOVAL OF GRILLE ASSEMBLY AND SPEAKERS

IMPORTANT:

MODEL: AS41W

Air Suspension speaker systems require a complete seal around all openings. Exercise caution in removal and replacement of speakers to insure air-tight seal. Commercial Mortite is used as a sealing compound.

- 1. The grille assembly is secured to the speaker housing by wire brads, not visible through grille cloth.
- 2. Fabricate an angle bracket tool similar to illustration as shown in figure A.
- 3. Using the tool described in step 2, insert and pry gently at each corner brad on one side of speaker housing.
- 4. Place fingers under center of grille assembly and pull straight upward to release remaining brads. Remove assembly from speaker housing.
- 5. Remove hex-head screws from speakers and lift from housing. Disconnect leads from speaker. Install replacement speaker observing correct phasing. Original Mortite can be reused by forming a head around rim.
- 6. To replace grille assembly:
 - A. Drive original brads into baffle to prevent air leakage B. Drive new brads into baffle through grille.


- REPLACEMENT PARTS LIST -


DESCRIPTION	SERVICE PART NO.
Cabinet - Grille Asm.	10-28165-1
- Nameplate	74-22923-3
Cord - Speaker	73-14921-1
Evelet - Jack Mounting	70-14635-2
Jack - Phono (SK1)	73-14854-1
- Nut	73-14854-2
- Lug	73-14854-3
- Washer	73-14854-4
Speaker – 4"PM (SP1)	12-22858-1

PERFORMANCE

Nominal System Impedance Recommended Amplifier Output Frequency Response System Resonance Enclosure Volume







AIR SUSPENSION SPEAKER

SERVICE

LITERATURE

YLVANI NERAL TELEPHONE & ELECTR

RADIO - TELEVISION STEREO HIGH FIDELIT

MODEL: AS41W

MODEL: AS41W AIR SUSPENSION SPEAKERS




FIGURE A

