

Sylvania Automatic Turntables



Professional Performance

from Sylvania automatic turntables

Sylvania component turntable systems help insure maximum performance from your favorite records. That's because Sylvania turntables feature equipment from industry leaders. Automatic changers from Dual, Garrard and BSR. Magnetic cartridges from Shure and Pickering. Each element of the turntable system selected by Sylvania to meet exacting performance specifications.

A new four channel automatic turntable brings you all the excitement of discrete four channel sound.

Three automatic turntables with deluxe stereo magnetic cartridges and highly compliant diamond styli for excellent stereo separation . . . exceptionally accurate sine wave response . . . lower tracking forces for less distortion . . . smaller tip mass for reduced record wear.

One automatic turntable with high-quality ceramic cartridge for the right combination of value and performance. Anti-skate control on all Sylvania turntables equalizes pressure on inner and outer walls of record groove, provides superior tracking, eliminates another source of distortion.

Plus cue-pause control to gently raise and lower tone arm to any band you choose.

Sylvania Turntables Are Complete Turntable Systems. Deluxe Cartridge, Base And Dust Cover Included On All Five Models.

Automatic Turntable

T4705W

professional design for
lower tracking forces

- Includes Dual 1225 changer with 4-pole induction motor
- Deluxe Shure M91ED magnetic cartridge with elliptical diamond stylus
- Removable cartridge holder
- Low mass, counterbalanced tubular tone arm with precision friction-free bearing suspension
- Calibrated stylus pressure adjustment
- Calibrated anti-skate control
- Bi-directional viscous-damped cue-pause control
- Single play manual spindle
- Output cables and AC cord attached
- Dust cover and base included
- Cabinet of Walnut grain vinyl on wood composition
Height 8¼" Width 17½" Depth 14¼"

Automatic Turntable

T3703W

deluxe magnetic cartridge

- Includes Garrard 6•300 changer with 4-pole induction motor
- Deluxe Pickering V15 magnetic cartridge with AT2 diamond stylus
- Low mass, counterbalanced tone arm
- Calibrated stylus pressure adjustment
- Calibrated anti-skate control
- Viscous-damped cue-pause control
- 45 RPM automatic adapter
- Single play manual spindle
- Output cables and AC cord attached
- Dust cover and base included
- Cabinet of Walnut grain vinyl on wood composition
Height 7¾" Width 16½" Depth 14¼"

Automatic Turntable

T4701W

excellent performance
in an economy turntable

- Includes full-size BSR turntable with 2-pole induction motor
- Deluxe ceramic cartridge with diamond stylus
- Low mass, tubular tone arm
- Calibrated stylus pressure adjustment
- Calibrated anti-skate control
- Cue-pause control
- 45 RPM automatic adapter
- Single play manual spindle
- Output cables and AC cord attached
- Dust cover and base included
- Cabinet of Walnut grain vinyl on wood composition
Height 7¼" Width 17¾" Depth 14¼"



Specifications

2 speeds—33 $\frac{1}{3}$ and 45 RPM
 Speed adjustment range of $\pm 3\%$
 7", 10" and 12" size selector
 Record capacity—6 records
 10 $\frac{1}{2}$ " turntable platter, 4.5 lbs., non-magnetic and dynamically balanced
 Recommended tracking pressure—.75-1.5 grams
 Wow and flutter—less than .12% RMS
 Rumble: 30 Hz 35 dB down
 60 Hz 45 dB down
 120 Hz 52 dB down



Specifications

Four positions for speed and record size:

| | |
|------------------|-----|
| 33 $\frac{1}{3}$ | 12" |
| 33 $\frac{1}{3}$ | 7" |
| 45 | 7" |
| 78 | 10" |

Record capacity—6 records
 10 $\frac{5}{8}$ " turntable platter
 Recommended tracking pressure—3.0 grams
 Wow and flutter—.15% RMS
 Rumble: 30 Hz 30 dB down
 60 Hz 40 dB down
 120 Hz 45 dB down



Specifications

3 speeds—33 $\frac{1}{3}$, 45 and 78 RPM
 7", 10" and 12" size selector
 Record capacity—6 records
 Recommended tracking pressure—3.5-4.5 grams
 Wow and flutter—less than .25%
 Rumble: 30 Hz 40 dB down
 60 Hz 35 dB down
 120 Hz 45 dB down

4-Channel Automatic Turntable

TQ3706

new 4-channel changer

- Includes BSR McDonald 510 changer with synchronous motor
- Pickering UV-15/2000 Q discrete 4-channel cartridge
- Low mass, counterbalanced anodized tubular tone arm
- Calibrated stylus pressure adjustment
- Calibrated anti-skate control
- Viscous-damped cue-pause control
- 45 RPM automatic adapter
- Single play manual spindle
- Output cables and AC cord attached
- Dust cover and base included
- Cabinet of Walnut grain vinyl on wood composition

Height 7 $\frac{1}{8}$ " Width 17 $\frac{3}{4}$ " Depth 14 $\frac{1}{4}$ "

Specifications

3 speeds—33 $\frac{1}{3}$, 45 and 78 RPM

7", 10" and 12" size selector

Record capacity—6 records

11" turntable platter

Recommended tracking pressure—3.0 grams

Wow and flutter—less than .1% RMS

Rumble: 30 Hz 40 dB down

60 Hz 45 dB down

120 Hz 47 dB down

The TQ3706 must be used with a CD-4 disc demodulator or a four channel receiver with a built-in CD-4 demodulator for discrete four channel records.



T2704W

This changer is available with a Shure M75-6S stereo cartridge as Model **T2704W**. All other features and specifications remain the same as Model TQ3706.

GTE SYLVANIA